

Graphing Calculators in Calculus

(Using a **TI-85** Calculator)

Gettysburg College

Summary of Graphing Calculators in Calculus

You should be able to perform easily and efficiently all of the following tasks on your individual graphing calculator:

1. Do arithmetic calculations.
2. Define and evaluate functions.
3. Graph functions, and change the viewing window in meaningful ways.
4. Trace the graph of a function.
5. Find zeros of a function.
6. Find intersection points of the graphs of two functions.
7. Make a function table from a formula.
8. Find maxima and minima of a function.
9. Find the derivative of a function at a point, and graph derivative over an interval.
10. Find the definite integral of a function over an interval (LHS/RHS).
11. Graph the slope field of a differential equation, and sketch a solution curve.

#1: Using a TI-85 Graphing Calculator

Introduction

Graphing calculators and computer graphing software are indispensable tools in studying and doing mathematics. For this course you are **required** to have a graphing calculator available to you at all times during class, when doing your homework, and while taking exams. Although any calculator from the following list is acceptable, we **very highly recommend** that you use a calculator from the **Texas Instruments TI-83/84** series.

Texas Instruments TI-81, TI-82, **TI-83/84** series, TI-85, TI-86, or TI-89

Casio fx/cfx-7000/9000 series

Sharp EL-9000 series

Hewlett-Packard 48/49 series

Class demonstration, instruction, and discussion will all utilize a calculator from the **TI-83/84** series. Although the other listed calculators can perform most of the desired operations, those calculators might be more difficult to use on some operations that are expected in the course. Handouts are available for all of the **Texas Instruments** calculators that are listed.

The purpose of handout #1 is to guide you through learning how to use the basic calculator features that are not related directly to functions and graphing. You will type or key-press the items in **bold**.

Keyboard Layout

Take a few moments to become familiar with the layout of the keyboard. The lower central portion has the numerical digits. Arithmetic operation keys are on the lower right side. The **arrow** keys form a rectangle on the top right. The **F1-F5** and **M1-M5** keys show as menu items on the screen. Just above most keys are printed two additional labels:

- (1) A yellow label which you can access by first pressing and releasing the yellow **2nd** key on the top left of the keyboard, and
- (2) A light blue letter or symbol label which you can access by first pressing and releasing the light blue **ALPHA** key on the top left of the keyboard.

Note: If your screen is blank when you press the **ON** key in the lower left corner, press and release the yellow **2nd** key once and then hold down the **up arrow** key to increase the screen contrast until you see something on the screen. Use the **2nd** and **down arrow** keys to reduce the contrast.

Arithmetic Operations

Practice the following calculations along with other similar calculations of your own design until you are comfortable and proficient with basic arithmetic calculations. After you type in each calculation to be done, press the **ENTER** key in the lower right corner of the keyboard. Use the **CLEAR**, **arrow**, and **DEL** (delete) keys to make typing corrections. Enter each of the calculations as one formula without breaking the formula down into simpler pieces.

$$5 + 7$$

$$3.6 - 8.25$$
 (Use the subtraction key on the right side, just above the addition key.)

$$4 \times 2$$
 (Note that multiplication is displayed on the screen by the "*" symbol.)

$$9 \div 4$$
 (Note that division is displayed on the screen by the "/" symbol.)

$$2^3$$
 (The ^ key, just above the \div key, is for exponents: 2^3 .)

$$-4 + 9$$
 (Use the negation (-) key on bottom row for negatives, NOT the subtraction key.)

$$3 \times -6$$
 (Use the negation key, NOT the subtraction key.)

$$2 + 3 \times 4$$
 (Where are the implied parentheses?)

$$(2 + 3) \times 4$$
 (Parenthesis keys are above the 8 and 9 keys.)

$$2 \times 3 + 4$$
 (Again, where are the implied parentheses?)

$$2 + 3 \div 4$$
 (Implied parentheses?)

$$(2 + 3) \div 4$$
 (Parentheses must be used to calculate $\frac{2+3}{4}$.)

$$2 \div 3 \times 4$$
 (What would you enter to calculate $\frac{2}{3 \times 4}$?)

When in doubt about which operations are performed first, either try a simple similar example or use parentheses to clarify what you intend. What should you enter to calculate $\frac{4+7}{2+3}$?

$$5^2$$
 (Press the 5 key first and then the x^2 key on middle left side.)

$$(3 + 4)^2$$

$$5^{-1}$$
 (Press 5, the 2nd key next, and then EE key with yellow x^{-1} label, near the 7 key.)

$$\frac{1}{2.4} \quad \frac{1}{2+3}$$
 (Try each twice: first use the \div key, and then use the 2nd x^{-1} key.)

- $\sqrt{4}$ (Press yellow **2nd** key first, then x^2 key with yellow $\sqrt{}$ label.)
- $\sqrt{12.25}$ (Parentheses are not necessary.)
- $\sqrt{9 + 16}$ (Parentheses are required.)
- $\sqrt{9} + \sqrt{16}$ (Is this result the same as the last result?)
- $\pi \div 2$ (To type π , press yellow **2nd** key first and then \wedge key with yellow label " π ".)
- $2 \times \pi$
- 2π (Omit the \times key on this and the next three examples;
- $3 \sqrt{4}$ these four examples illustrate "implied" multiplication.)
- $2 (3 + 4)$
- $1 / 2 \pi$ (Is the result what you expected?)

Last Entry

Type again the calculation $2 (3 + 4)$ and press the **ENTER** key. Now press the yellow **2nd** key and then the **ENTER** key with the yellow **ENTRY** label above it. Notice that your last formula entered reappears on the screen for you to make changes. Use the **arrow** keys to change the "3" to a "5" in order to compute $2 (5 + 4)$. Press the **ENTER** key as usual to carry out the calculation.

Edit your last entry (**2nd ENTRY**) again by first placing the flashing rectangular cursor over the digit "5" (use **left arrow** key). Press the **2nd** key and then the DEL key with the yellow label **INS**. You are now in the "insert" mode instead of the "typeover" mode. Notice that the cursor is a flashing underline rather than a rectangle. Press the **3** key and notice what happens. Then press the **7** key. If you press an **arrow** key, the cursor goes back to the typeover mode as indicated by the flashing rectangular cursor. Press the **ENTER** key. (The cursor does not have to be at the end of the formula.)

Note: Since we've become aware of different cursor styles, watch what happens to the cursor style when you press the yellow **2nd** key. Press the **2nd** key again and watch. If you ever mistakenly press **2nd**, you can cancel by pressing **2nd** again. Look at the cursor to see whether **2nd** is activated. Similarly, watch the cursor style as you slowly press the **ALPHA** key. There is a cycle of three possibilities. Try pressing the **7** key four times after each of the three possibilities. (Don't press the **ENTER** key, and when you have tried all three press the **CLEAR** key.) What did you observe? (After each of the three possibilities, press the **CLEAR** key, but NOT the **ENTER** key.)

Variables

Type the calculation: $2 + 3$ ENTER. Notice that the answer is 5. Now press the \times key and the 4 key. The display screen reads "Ans*4". What is the result when you press ENTER?

"Ans" is a variable that stores your last calculated value (as opposed to your last entered formula). Now enter $50 - \text{Ans}$. (Press **2nd** key and then ANS key in lower right corner of keyboard.) The value of the variable Ans changes after each new formula calculation.

If you wish to calculate again the last formula entry without editing it, just press the ENTER key -- as many times as you wish to perform the calculation.

Example: Press 3 and then the ENTER key. The value of Ans is now 3.

Type $2 \times \text{Ans}$ ENTER. (Use the **2nd** and ANS keys.) The value of Ans is now 6.

Press the ENTER key repeatedly to see the value of Ans repeatedly doubled.

The result of each calculation is automatically stored in the variable Ans. Values can also be stored in single-letter variables by using the **STO>** key located in the lower left corner of the keyboard. Carry out the following example entries and observe what happens:

5 STO> A	ENTER	(STO> key flips cursor to ALPHA; just press key with label A.)
2 + A	ENTER	(Press the ALPHA key and then the key with label A.) (The value stored in variable A is used in the calculation.)
A \div 2 STO> B	ENTER	(The value of A/2 is displayed and also stored in variable B.)
A \times B	ENTER	(Current values of variables A and B are used in calculation.)
7 STO> A	ENTER	(The value of A is changed, but formula A/2 is not recalculated.)
B	ENTER	(Value of B did not change when a new value was stored in A.)

Experiment with other examples using variables to be sure you understand how they work in formulas and calculations.

You should practice repeatedly all the features discussed in this handout (and each later handout) until you are comfortable and proficient with them. You must be able to use these features easily and efficiently. These handouts show you the most important features you will need in calculus. Consult your calculator manual for further details and features.

#2: Functions and Graphing on a TI-85 Calculator

The purpose of handout #2 is to learn how to define, evaluate, and graph functions with your calculator. A TI-85 calculator can work simultaneously with up to 99 user-defined functions. Our first example will be the linear function $y = f(x) = x - 2$. Type or key-press the items in **bold**.

DEFINE the function by pressing the **GRAPH** key and then the **y(x)=** key. Type **x - 2** after the equal sign. Use the key labeled "**x-VAR**" to type the independent variable. (Remember **CLEAR**, **DEL**, **INS**, and **arrow** keys to edit.) Press the **EXIT** key twice or **2nd QUIT** to get back to the Home Screen.

Note 1: In function mode you must use the letter "x" as the name of the independent variable for any "y =" function, no matter what the independent variable might be named in your actual problem. For example, if your problem uses $g(p) = p^2$, you must use $y1 = x^2$ on the calculator.

EVALUATE the function you have defined by using *y1* as the name of the dependent variable. To type the "*y1*" symbol, press the **2nd alpha** keys to type lower case. Notice the cursor style. Then press the letter **Y** on the zero key. Practice the examples, and observe the output. Remember that our example function is subtraction of 2 from the value of the independent variable *x*.

3 STO> x (We want to evaluate $f(3)$, that is, $f(x) = x - 2$ when $x = 3$)

y1 (The value of *y1* depends upon the current value of *x*, namely 3.)

6 STO> x : y1 (A one-line short cut. Use **2nd** and **.** (period) keys to get colon **:**.)

4 STO> x : 5 y1 + 3 (Notice the implied multiplication.)

Note 2: The symbol "*y1*" is used as the name of the dependent variable (whose current value depends upon the current value of the independent variable "*x*").

Note 3: An alternate way to compute the value of a function at a specific point, $f(6)$ for example, is to type **evalF(y1 , x , 3)** on the Home Screen or within an expression. (Press **2nd CALC** to get to **evalF**.) Use **2nd ENTRY** to edit the last expression to: **5 evalF(y1 , x , 4) + 3** and **ENTER**.

GRAPH the function you have defined by pressing the **GRAPH ZOOM MORE ZDECM** keys. The graph of your function is plotted in a viewing window that extends from -6.3 to 6.3 along the x -axis and from -3.1 to 3.1 along the y -axis. Tick marks are placed every 1 unit along each axis. Press the **RANGE** key on the top row to see these specifications for the viewing window. The variables $xMin$, $xMax$ and $yMin$, $yMax$ describe the extent of each coordinate axis. The variables $xScl$ and $yScl$ describe the numerical distance between tick marks along these axes. The values of the window variables may be changed, but we will not do so at this time.

Press the **GRAPH** key on the top row to see the graph again. Use the **arrow** keys to move the *free-moving cursor* (+ sign) around the viewing window. Notice the x - and y -coordinates of the point at the center of the cursor. Use the free-moving cursor to write down the coordinates (with comma and parentheses) of three sample points of your choice from the graph of the function.

Press the **TRACE** key on the top row. You will see the X-shaped *trace cursor* on the graph of the function. Notice also the x - and y -coordinates of the graph point located at the cursor. Use the **right** and **left arrow** keys to move the trace cursor along the graph of the function. Notice in this example that the y -coordinate is always 2 less than the x -coordinate. If you press the **ENTER** key, the viewing window will be made to center on the trace cursor. Press the **RANGE** key to see the new values of the viewing-window variables. Choose **ZOOM MORE ZDECM** to reset the original viewing window. Experiment with what happens when you press the **EXIT**, **QUIT**, **GRAPH**, **TRACE**, **CLEAR**, and **ZOOM ZDECM** keys from various different screens.

Note 4: The trace arrow keys restrict the possible x -coordinates of the points that can be specifically computed since the trace cursor moves in jumps from one screen pixel (tiny, square picture element) to another. To compute the value of the function and plot the corresponding graph point at arbitrary values of x :

Press **GRAPH MORE MORE EVAL** keys.

Type the desired value of x (Eval $x = 1.325$ for example) and press the **ENTER** key.

Note 5: More than one function can be defined and graphed at the same time. We will use $y = g(x) = 1 - x$ as our second example function.

Press **GRAPH y(x)= ENTER** to get down to the line "y2=". Type **1 - x** and press **GRAPH**.

Press **TRACE**. Move trace cursor to the point where $x=.7$, and watch what happens when you press **up** and **down arrow** keys. Notice the number in upper right corner of screen.

Now press **GRAPH MORE MORE EVAL** and enter **2.637** for the value of x . Again watch what happens when you press the **up** and **down arrow** keys.

#3: Changing the Viewing Window on a TI-85 Calculator

The purpose of handout #3 is to learn how to move the viewing window around the coordinate plane. Our two examples are the following exponential functions: $y = f(x) = 0.5(2^x)$ $y = g(x) = 2(0.4)^x$

SELECT functions for graphing by pressing the **GRAPH** and **y(x)=** keys, **CLEARING** any previously defined functions, and entering $.5 * 2 ^ x$ for $y1$ and $2 * .4 ^ x$ for $y2$. Since the $y1$ and $y2$ functions have highlighted equal signs, they are "selected" for graphing. Press **GRAPH ZOOM MORE ZDECM** keys and notice the moving dots in the upper right corner of the screen indicating that the calculator is busy working.

Go back to **y(x)=**. Press the **SELCT** key to "deselect" $y1$ by turning off the highlighted equal sign. Press the **SELCT** key once again to "select" $y1$. Press the **down arrow** key and deselect $y2$. Press **2nd GRAPH** and observe only one function graph (which one?). Although the deselected $y2$ function is not plotted, it is still defined and can be used and evaluated from the Home Screen.

Go back to **y(x)=** and select both $y1$ and $y2$. Press **2nd GRAPH**. While graphing, press the **ENTER** key to pause and resume, or the **ON** key to stop. Observe the possible values of x and y when you use the **arrow** keys to move the free-moving cursor.

CHANGE the viewing **RANGE** to make x vary from -2 (negation key, not subtraction key) to 4 with tick marks every 1 unit and to make y vary from -2 to 8 with tick marks every 2 units. **GRAPH**. What is different about the values of x and y when you now use the **arrow** keys to move the free-moving cursor? The previous **ZOOM ZDECM** had set the window variables so that the pixel steps are 0.1 in all directions. Most other choices for values of the window variables lead to more awkward sizes for the pixel steps. **TRACE** uses the pixel steps for x -coordinates and computes the function values to get y -coordinates. **EVAL** allows you to type in whatever x -coordinate you wish and computes the function value to get the y -coordinate. Experiment with trying different values of the window variables and using **TRACE** and **EVAL**.

ZOOMING is a shortcut to making certain kinds of changes in the values of the window variables. Choose **ZOOM ZDECM** to set the particularly nice values for the window variables. We can also zoom in and out from whatever is our current viewing window. To set zooming factors press the **ZOOM MORE MORE ZFACT** keys. Change both the $xFact$ and $yFact$ variables to have the value **2** instead of 4.

ZOOM IN: Press the **ZOOM** and **ZIN** keys, press the **ENTER** key to accept the origin as the zoom center, and when graphing is finished press the **CLEAR** key to stop further zooming. Use the **arrow** keys to move the free-moving cursor, and observe that the pixel steps of 0.05 are exactly half of the previous 0.1 pixel steps. Tick marks appear farther apart on the screen, but actually represent the same numerical distance as before the zoom. Press **GRAPH RANGE** and notice that zooming has multiplied the previous min and max values by $\frac{1}{2}$ but has not changed the scale values for tick marks. Change the scale values to .5, and view the **GRAPH**.

ZOOM OUT: Press the **ZOOM** and **ZIN** keys. Use the **arrow** keys to move the free-moving cursor to the point **(1.5, 1)**. Press the **ENTER** key to zoom out centered on this point. Observe how the axes are off-center. When the graphing is finished, press **ENTER** again to zoom out again on the same point. Finally, press **CLEAR** to stop further zooming. In **GRAPH RANGE**, change both scale variables to 2, and press **GRAPH**.

ZOOM BOX: An alternate method of zooming in is to form a rectangular box to be the new viewing window. Let's apply this method to zoom in on the point of intersection of our two example function graphs. Choose **ZOOM BOX**. Use the **arrow** keys to move the free-moving cursor to any corner of the new viewing rectangle desired. Press the **ENTER** key. Then use the **arrow** keys again to move the cursor to the opposite corner of that rectangle, and press **ENTER**. Keep making new **BOX** selections repeatedly until the x - and y -coordinates of the cursor do not change in, say, the fifth decimal place as the cursor is moved one pixel step in each direction. Write down (using comma and parentheses) the intersection point with coordinates rounded to four decimal places.

Answer: (0.8614, 0.9084)

Note 1: None of the zooming commands affect the scale values, that is the numerical distances between tick marks on the axes. After you have zoomed in and/or out to obtain the viewing window you desire, you may then want to press **RANGE** and enter suitable values for $Xscl$ and $Yscl$. You may also wish to "clean up" the values of $Xmin$, $Xmax$, $Ymin$, and $Ymax$. Press **GRAPH** to view the results.

Note 2: Reset the **ZOOM ZDECM** viewing window. If you wish grid dots displayed within the viewing window, choose **GRAPH MORE FORMT**. Then use **arrow** keys to highlight **GridOn** with the flashing rectangle, and press **ENTER**. Finally, press **GRAPH** to see the result. **GRAPH MORE FORMT** can also be used to turn off the grid dots and make other changes in how the viewing window looks.

#4: Formula Tables and Data Plots on a TI-85 Calculator

The purpose of handout #4 is for you to learn how to use formula tables and data plots. Our example exponential function has formula $y = 0.5(2^x)$. You should press the $y(x)=$ key and enter this formula for $y1$ as before. The example data table is given to the right. We will enter this data into the calculator after we learn how to use a formula table.

x	y
-2	3.05
-1	2.55
0	1.94
1	1.64
2	1.25
3	1.07
4	0.84

FORMULA TABLES

The TI-82, TI-83/84, and TI-86 calculators have a powerful and flexible table feature. Some of that power can be mimicked on the TI-85 by writing a program to do similar things. The following program is a very simple program that captures some of the table features, but it is not very flexible. If you are interested in a more powerful and flexible table program for a TI-85 calculator, see the supplementary handout **#4A: Another Table Program for the TI-85 Calculator**.

First we must enter the program. Press the **PRGM** and **EDIT** keys. (Note that the cursor is in the **ALPHA** style, so you should NOT press the **ALPHA** key when you type in the program name.) Type the name **TBL** for this short program, and press **ENTER**. Type in the program itself using the key-press hints given in parentheses. Press the **ENTER** key at the end of each line. Remember to press the **ALPHA** key to type an alphabetic letter or light blue symbol. Press **ALPHA** twice to lock caps, and once again to turn caps off. If you need to make corrections, use the **INS**, **DEL**, and **arrow** keys in the natural way.

```

Prompt START , STEP (Press I/O and Prompt.)
{ 6 , 2 } → dim T (2nd LIST to type { and }. 2nd MATRIX OPS to type dim.)
Fill( 0 , T ) (2nd MATRIX OPS to type Fill)
START → x (Press STO> to type →.)
For( I , 1 , 6 ) (EXIT CTL or 2nd CTL to type For.)
x → T ( I , 1 )
y1 → T ( I , 2 ) (2nd ALPHA to type lower case y.)
x + STEP → x
End (End is in the CTL submenu.)
Disp T (2nd I/O to type Disp.)

```

When you have finished typing in the program, press the (2nd) **QUIT** key.

Before you execute the **TBL** program, be sure you have entered a specific function for $y1$. This table program uses ONLY the $y1$ function. From the Home Screen, press the **PRGM** and **NAMES** keys, select the **TBL** program (you may need to use **MORE**), and press **ENTER**. At the first question mark, type a starting value of 0 for x , and press **ENTER**. At the second question mark, type a step size of .5, and press **ENTER**.

The first column of the table gives values for x , and the second column gives the corresponding values of $y1$. Press the **ENTER** key (repeats the last command) to make another table starting at -2 and using .0001 for the step size. To display any hidden parts of the table on the Home Screen, press (**Alpha**) **T** and **ENTER** keys, and use the **left/right arrow** keys to scroll.

DATA PLOTS

Before making a data plot, deselect all of the functions defined by formulas under **y(x)=**. You may do this either by pressing the **SELCT** key on each function line or by choosing **MORE ALL-** from the **y(x)=** submenu.

Press the **STAT** and **EDIT** keys. Press **ENTER** twice to accept the two list names. Then press **CLRxy** to clear the lists for new data. Type in (alternately) the values for x and y from the given data table. Press (**2nd**) **QUIT** when you are finished. For the given data points, enter a suitable set of **GRAPH RANGE** values such as -5, 5, 1 for x and 0, 5, 1 for y (*Min, Max, Scl*). **QUIT**. Press the **STAT DRAW SCAT** and **CLEAR** keys. The data plot is easily erased, so you may have to plot it again.

MODEL THE DATA using a function defined by a formula. You can use trial and error to determine possible values for the parameters a and b in the family of exponential functions with formula $y = b \cdot a^x$ so that the graph of the function fits the data points as best as you can make it. The specific formula should be entered as one of the selected **y(x)=** functions. For example, start by entering the formula 2.1×0.7^x for the function $y3$. Again press **STAT DRAW SCAT** and **CLEAR** to see how well this specific model fits the given data. Modify the values of the parameters a and b to try to get a better fit.

#4A: Another Table Program for the TI-85 Calculator

This handout is a supplement to handout #4 for the TI-85 calculator. The program listed below is adapted from a program by Marco Radzinski and is more powerful and flexible than the simple table program presented in the main handout. You may either type the program directly into your own calculator or transfer the program to your calculator from another calculator by linking.

TYPE IN THE PROGRAM

1. Press the **PRGM** key and select **EDIT**.
2. Type in the name of your new program (**TABLE**), and press the **ENTER** key. (Note that the flashing cursor is set into the **ALPHA** mode so you can just press the keys corresponding to the letters in the program name.)
3. Type in the program itself using the key-press hints given in parentheses. Press the **ENTER** key at the end of each line. Remember to press the **ALPHA** key to type an alphabetic letter. If you need to make corrections, use the **INS**, **DEL**, and **arrow** keys in the natural way.

Func : CILCD	(2nd MODE, Func , ENTER . I/O MORE CILCD .)
{ 1 , 1 } → dim T : Fill(0 , T)	(2nd LIST for { }. 2nd MATRX OPS for dim , Fill)
InpSt 'Function(s):', Fs	(I/O MORE InpSt)
"{" + Fs → F	(STO> to type →)
St>Eq(F , F)	(2nd STRNG St>Eq)
dimL F → N : I = 1	(2nd LIST OPS dimL)
For(x , xMin , xMax , xScl)	(2nd CTL. GRAPH RANGE xMin xMax xScl)
{ I , N + 1 } → dim T	
x → T (I , 1)	
F → ys	
For(J , 1 , N)	
ys (J) → T (I , J + 1)	
End : I + 1 → I : End	(CTL End)
CILCD	(I/O MORE CILCD to clear LCD screen)
Output(8 , 1 , 'x,' + Fs)	(I/O Output)
Pause T	(CTL MORE MORE Pause)

4. When you have finished typing in the program, press the **2nd QUIT** key.
5. If you need to modify the program after you have typed it into the calculator, press the **PRGM** and **EDIT** keys, and select the program you want to modify. Use the **INS**, **DEL**, and **arrow** keys in the natural way to help you make any changes.

TRANSFER THE PROGRAM BY LINKING

1. Find someone who has this TABLE program, such as Professor Flesner.
2. Attach the LINK cable to both calculators. Be sure the cable is pushed in *very firmly*.
3. Turn on both calculators, and press **2nd LINK** on each. On the "destination" calculator, press the **RCV** key to be ready and *waiting...* to **RECEIVE** the programs.
4. On the "source" calculator, select **SEND PRGM**, highlight the desired program name (**TABLE**), and press **SELCT**. Those items selected for transmission are marked with a **■**. Press the **XMIT** key to transmit the selected program.
5. After the transmission is "Done", press **2nd QUIT** on both calculators, turn both calculators **OFF**, and remove the link cable.

EXECUTE THE PROGRAM

0. First be sure your calculator has the program, either type in or transferred by linking.
1. Enter all of the **y(x)=** functions that you are going to use.
2. Press the **GRAPH RANGE** keys, and enter values for *xMin*, *xMax*, and *xScl*. These should be the smallest and largest values of *x* in the table and the step size for *x*.
3. From the Home Screen, press the **PRGM NAMES** keys, select the **TABLE** program (you may need to use **MORE**), and press **ENTER**. Wait a second or two.
4. After the "Function(s):" prompt, type a list of function names (separated by commas) in the order that you wish them to appear in the table, for example: **y1 , y4 , y3**
Be sure to use the **2nd ALPHA** keys before each letter "y" so that you get lower case.
5. Press the **ENTER** key, and wait several seconds for the table to appear. The column headings appear in the lower left corner of the screen. Use the **arrow** keys to scroll all around the table.
6. When you are finished viewing the table, press the **ENTER** key and see the word "Done". If you wish to scroll further through the table, type **(ALPHA) T** on the home screen and press the **ENTER** key. Use the **arrow** keys to scroll through the table as before.
7. Before you execute the program again, be sure to update any **y(x)=** definitions and the **RANGE** values for *x*. If no commands have been entered from the Home Screen since you last ran the program, then you can re-run the program simply by pressing the **ENTER** key.
8. If a "02 DIV BY ZERO" error occurs, then the **RANGE** needs to be changed to values of *x* that are in the domain for all functions listed. Before you execute the program again with the desired function(s), clear the error condition by executing the program and typing the zero function: **0**.

#5: Left and Right Sums on a TI-85 Calculator

The purpose of handout #5 is to implement the computation of left- and right-hand sums on the calculator. Suppose we wish to estimate the area under the graph of $f(x)$ over the interval from $x=a$ to $x=b$ by forming the appropriate left-hand and right-hand sums for various values of n . For any choice of n , the increment in x would be $h = \frac{b-a}{n}$, and the equally spaced values of x would be

$$\left\{ \begin{array}{l} a = x_0 \\ x_1 = x_0 + h = a + h \\ x_2 = x_1 + h = a + 2h \\ x_3 = x_2 + h = a + 3h \\ \vdots \\ b = x_n = x_{n-1} + h = a + nh \end{array} \right.$$

Given $f(x)$, a , b , and a choice for n , the left- and right-hand sums, L and R , may be written:

$$L = \sum_{i=0}^{n-1} f(a+ih) \cdot h \quad \text{and} \quad R = \sum_{i=1}^n f(a+ih) \cdot h, \quad \text{where } h = \frac{b-a}{n}.$$

Notice that the only dissimilarity between the left-hand sum and the right-hand sum is in the lower and upper limits of summation. Finally, as the value of n becomes arbitrarily large, the values of L and R both approach the area under the graph of the function $f(x)$ over the interval $a \leq x \leq b$.

To implement the computation of left-hand sums on the calculator, we will write a program, that is, a list of the steps for the calculator to do. We need to type the program into the calculator only once. Then to compute a left-hand sum, we define the particular function and request the calculator to perform the program steps ("execute the program"). We can similarly implement the computation of right-hand sums. A brief *outline* of the program we will create later is as follows:

- Prompt for values of the parameters a , b , and n .
- Compute the increment, $h = \frac{b-a}{n}$.
- Starting with a sum of zero, repeatedly add each new product $f(a+ih) \cdot h$ to the previously accumulated sum.
- Display the final sum.

CREATE NEW PROGRAMS by typing program instructions into the calculator:

- Press the **PRGM** key and select **EDIT**.
- Type in the name of your new program (**LHS**), and press the **ENTER** key. (Note that the flashing cursor is set into the **ALPHA** mode so you can just press the keys corresponding to the letters in the program name.)

- Type in the program itself using the key-press hints given in parentheses. Press the **ENTER** key at the end of each line. Remember to press the **ALPHA** key to type an alphabetic letter. If you need to make corrections, use the **INS**, **DEL**, and **arrow** keys in the natural way.

Prompt A , B , N (Press the **I/O** menu key and then the **Prompt** menu key.)

(B - A) / N → H

0 → L

For(I , 0 , N - 1) (Press the **CTL** menu key and then the **For** menu key.)

A + I * H → x

L + y1 * H → L (Press the **2nd VARS**, **MORE**, and **EQU** keys. Select **y1**.)

End (Press the **CTL** menu key and select **End**.)

Disp L (Press the **I/O** menu key and select **Disp**.)

Stop (Press the **CTL** menu key, press **MORE** twice, and select **Stop**.)

- When you have finished typing in the program, press the **2nd QUIT** key.
- To type in the program for computing right-hand sums, repeat the instructions in steps 1-4. Use **RHS** for the name, replace "**L**" by "**R**" everywhere, and change the For statement to:
For(I , 1 , N)
- If you need to modify a program after you have typed it into the calculator, press the **PRGM** and **EDIT** keys, and select the program you want to modify. Use the **INS**, **DEL**, and **arrow** keys in the natural way to help you make any changes. When you are finished, press **2nd QUIT** key.

EXECUTE PROGRAMS LHS and RHS to approximate, for example, the area under the graph of $f(x) = x^3$ over the interval from $x = 1$ to $x = 3$, using $n = 100$ subdivisions:

- Enter the formula x^3 as the $y1$ function. Remember that LHS and RHS were written to use only the $y1$ function.
- Press the **PRGM** and **NAMES** keys. Select the **LHS** program, and press the **ENTER** key to execute the program from the Home Screen.
- Enter the values **1**, **3**, and **100** (one value at each question mark) for the values of the parameters a , b , and n .
- Wait until the calculation is **Done**. (Answer should be 19.7408.)
- Repeat steps 2-4 to compute the corresponding RHS. (Answer should be 20.2608.)
- Enter the formula $(L + R) / 2$ on the Home Screen to compute the average of the left- and right-hand sums. (Answer should be 20.0008.)

#6: Calculus Features on a TI-85 Calculator

In addition to the operations that we have previously learned (see earlier handouts), there are some powerful features on a TI-85 calculator that provide shortcuts to various calculus calculations. There are two major ways to carry out most of these calculations:

- Commands executed from the home screen or included in $y(x)$ = function definitions, and
- Interactive calculations on the graphing screen.

Consult your TI-85 calculator manual for further details of features discussed below and many more!

For this handout, define example functions $f(x) = x^3 - 3x^2 + 2.5$ $g(x) = x - 0.4$ and respectively. Graph both functions using **ZOOM MORE ZDECM**. Use \triangleright and \triangleleft to change the value of x . Type or key-press items in **bold**.

1. *Evaluate a function.* For example, compute $f(1.6183)$ and $g(1.6183)$. (Ans: -1.11853 and 1.2183)

Home Screen: Enter **1.6183 STO> x : y1** or **CALC evalF(y2 , x , 1.6183)** as we did before.

Interactive: **GRAPH MORE MORE EVAL** Eval $x = 1.6183$ Use \triangle and ∇ to switch functions.

Notes: **GRAPH TRACE** gives function evaluation, but only at pixel-based points.

The **TBL** and **TABLE** programs provide another way to evaluate functions.

2. *Find zeros of a function.* For example, the first of three zeros of $f(x)$ lies between -1 and 0 at about -0.5 for x .

Interactive 1: Press the **2nd SOLVER** key, and type eqn: **y1 = 0 ENTER**. (**ALPHA STO>** for =)
 $x = -0.5$ **ENTER** bound = **{ -1 , 0 }** (Use **2nd LIST** to type { and }.)

Arrow up to the line "x = -.5" in order to solve for the variable x.

Press **SOLVE**, and see $x = -0.81003792923396$ is a zero of $f(x)$.

Change the bound values and arrow to "x =" to find the other two zeros.

Interactive 2: **GRAPH MORE MATH** Set **LOWER** bound to **-1** and **UPPER** bound to **0**.

Set **ROOT** approximation to **-0.5**. Use \triangle , ∇ to select $y1$ (see upper right corner).

Press **ENTER**, and see root value $x = -0.810379292$ as a zero of $f(x)$.

3. *Find intersection points of two graphs.* For example, the first of the three intersection points of $f(x)$ and $g(x)$ is at about -1 for x .

Interactive 1: **2nd SOLVER**. Press **up arrow** key to edit eqn: **y1 - y2 = 0 ENTER**.

Use initial guess $x = -1$ and bound = **{ -2 , 0 }**, go up to "x =", and **SOLVE**.

See $x = -0.9873808183822$ at the intersection point. **QUIT** to the Home Screen.

y1 ENTER. See $y = -1.38738081838$ at the intersection point.

Interactive 2: **GRAPH MORE MATH** Set **LOWER** bound to **-2** and **UPPER** bound to **0**.

MORE ISECT. Set guess $x = -1$, and use \triangle , ∇ and **ENTER** to select two curves.

Note: Repeated use of **TRACE** and **ZOOM** (as we did in earlier handout) is a much longer process for finding zeros of a function and intersection points.

4. Find local maxima and minima of a function on an interval. For example, find the single local maximum or single local minimum of the function $f(x)$ on the interval $[1,3]$, if there is one.

Home Screen: **CALC MORE fMax(y1,x,1,3)** See 3 (rounded) as value of x making $f(x)$ largest.
CALC evalF(y1, x, Ans) See 2.5 (rounded) as that maximum value of $f(x)$.

Interactive: **GRAPH MORE MATH** Set **LOWER** bound to **1** and **UPPER** bound to **3**.
MORE FMIN. Set guess $x = 2.5$, use Δ , ∇ to select $y1$, and press **ENTER**.
 See $x = 2$ (rounded) and $y = -1.5$ at minimum point for $f(x)$ over interval $[1,3]$.

5. Find and graph the derivative of a function. For example, compute $f'(2.5)$ and graph $f'(x)$.

Home Screen: **2nd CALC nDer(y1, x, 2.5)** See 3.750001 as approximate value of $f'(2.5)$.

Note: nDer uses a central difference quotient with 0.001 as the default value of h .

2nd TOLER $\delta = .0005$ EXIT ENTER gives 3.75000025 with 0.0005 as value of h .

y(x)= Screen: Define $y3 = 2nd\ CALC\ nDer(y1, x, x)$ and **GRAPH ZOOM MORE ZDECM** to graph.
 $y3$ can be used as $f'(x)$ for computation and graphing. Deselect $y3$ in **y(x)=**.

Interactive: **GRAPH MORE MATH dy/dx**. Use Δ and ∇ to select function $y1$ (see upper right).
 Set $x = 2.5$ **ENTER**. See 3.75 as approximate value of dy/dx at given point.

Note: The interactive method for derivatives is restricted to pixel-point values for x .

6. Find the definite integral of a function over an interval. For example, compute $\int_{0.2}^{2.0} f(x) dx$.

Home Screen: **2nd CALC fnInt(y1, x, .2, 2)** and see 0.5076 as value of the definite integral.

Interactive: **GRAPH MORE MATH $\int f(x)$** Use Δ and ∇ to select function $y1$ (upper right).

Set $x = .2$ **ENTER**. Set $x = 2$ **ENTER**. (Restricted to pixel-point limits)

See 0.5076 as value of integral.

7. Draw on the graphing screen.

Use **GRAPH MORE DRAW MORE CLDRW** to clear any previous drawings. Deselect $y2$ in **y(x)=**.

GRAPH MORE DRAW DrawF y1 - 2 ENTER. Temporary graph of $f(x) - 2$. (CLDRW)

GRAPH MORE DRAW DrInv y1 ENTER. Graph of inverse relation for $f(x)$.

This example inverse relation is not a function since $f(x)$ is not invertible. (CLDRW)

8. Draw tangent lines to graph of a function. For example, draw the tangent line to the graph of $f(x)$ at $x = 2.2$. Be sure that only $f(x)$ is selected on the **Y=** screen.

Home Screen: **GRAPH MORE DRAW MORE MORE TanLn(y1, 2.2) ENTER**. (CLDRW when done.)

Graphing Screen: **GRAPH MORE MATH MORE MORE TANLN**. Set $x = 2.2$, and press **ENTER**.

#7: Differential Equations on a TI-85 Calculator

The purpose of handout #7 is to implement graphing the slope field of a differential equation and sketching an approximate solution curve using Euler's method. The programs for graphing a slope field and for using Euler's method may either be typed into your calculator by hand or transferred from another calculator by linking. Type or key-press items in **bold**. (See calculator manual for more differential equations features.)

TRANSFER THE PROGRAMS BY LINKING

1. Attach the LINK cable to both calculators. Be sure the cable is pushed in *very firmly*.
2. Turn on both calculators, and press **2nd LINK** on each. On the "destination" calculator, press the **RCV** key to be ready and *waiting...* to **RECEIVE** the programs.
3. On the "source" calculator, select **SEND PRGM**, highlight the desired program name(s), and press **SELCT** to select each one desired. Those items selected for transmission are marked with a **■**. Press the **XMIT** key to transmit the selected program(s).

EXECUTE THE PROGRAMS

0. First be sure your calculator has the program, either transferred by linking (described above) or typed in (described below).
1. In the window $-4 \leq x \leq 4$ and $-3 \leq y \leq 3$, let's use the example differential equation $\frac{dy}{dx} = x + y$
2. Press **GRAPH y(x)=** and enter the expression $x + y$ after the "y1=". Press **RANGE** and enter the appropriate values for the x and y intervals, using a scale value of 1 in each direction.
3. Press the **PRGM**, **NAMES**, and **SLOPE** keys. Press the **ENTER** key to execute the **SLOPEFLD** program from the Home Screen.
4. Watch the slope field being graphed. When finished, press **2nd QUIT**.
5. Press the **PRGM**, **NAMES**, and **EULER** keys. Press the **ENTER** key to execute the **EULER** program from the Home Screen.
6. Type **1** and **ENTER** at the first prompt to keep the plotted slope field in the viewing window. Enter **-1** for the initial value of x and **.2** for the initial value of y . Enter **2** to graph a solution curve in both directions from the initial point. When finished, press **2nd QUIT**.
7. Press the **ENTER** key to repeat the Euler program, type **0** at the first prompt to clear the viewing window, and use the same initial point to make a graph in both directions. **2nd QUIT**.
8. Without clearing the viewing window, repeat the Euler program several times using different initial points and choices for the direction(s) to graph from the initial point.

TYPE IN THE PROGRAMS

1. The slope field program is adapted from a program by Mark Howell that appears on page 113 of *Technology Resource Manual for Calculus* by Finney, Thomas, Demana, and Waits.
2. See handout #5 for general instructions on creating new programs on the TI-85. Note that the x and y variables are lower case.
3. Some of the new key-press combinations for the TI-85 are: For the lower case x, y variables and for **FnOff**, use **GRAPH VARS** and **MORE MORE**. For **CIDrw** and **Line**, use **GRAPH MORE DRAW** and **MORE**. For **DispG** and **Input**, use **I/O**. For **Lbl**, **Goto**, **For**, **If**, **While**, use **CTL** and **MORE**. For **<**, **>**, and **==**, use **2nd TEST**. For **xMin**, **xMax**, **yMin**, **yMax**, and **Δx** , use **VARS MORE MORE RANGE**. For **"**, use **2nd STRNG**. For **abs**, use **2nd MATH NUM**.

SLOPE FIELD PROGRAM (SLOPEFLD)

```
14 - L
18 - W
(yMax - yMin) / L - V
(xMax - xMin) / W - H
FnOff
CIDrw
DispG
yMin + V / 2 - y
For ( R , 1 , L )
xMin + H / 2 - x
For ( C , 1 , W )
y1 - M
- M * H / 2 + y - S
M * H / 2 + y - T
If abs ( T - S ) > V
Then
y + V / 2 - T
y - V / 2 - S
( T - y ) / M + x - Q
( S - y ) / M + x - P
Else
x - H / 2 - P
x + H / 2 - Q
End
y - Y
Line ( P , S , Q , T )
Y - y
x + H - x
End
y + V - y
End
```

EULER'S METHOD PROGRAM (EULER)

```
Disp "TO CLEAR WINDOW "
Input "ENTER 0 : ", C
If C == 0
CIDrw
FnOff
Input "INITIAL x : ", P
Input "INITIAL y : ", S
Disp "1 LEFT , 3 RIGHT , "
Input "2 BOTH : ", C
If C < 2
Goto L2
P - x
S - y
While x < xMax
x +  $\Delta x$  - Q
y + y1 *  $\Delta x$  - T
Line ( x , y , Q , T )
Q - x
T - y
End
Lbl L2
If C > 2
Goto L4
P - x
S - y
While x > xMin
x -  $\Delta x$  - Q
y - y1 *  $\Delta x$  - T
Line ( x , y , Q , T )
Q - x
T - y
End
Lbl L4
DispG
Stop
```